

Planar®-N

The smallest console remote control in the NBB product range, available in various versions.



Technical information

Frequency band (F-Band): 434,050 – 434,750 Mhz

Frequency band EU (G-Band): 866 – 870 MHz


Frequency band USA: 915 MHz

RF output: < or = 10 mW

Operating range: ≤ 300 m

Antenna: integrated

Response time of control command: 15 ms

SMJ-Technology : –

Advance alert "battery empty": 15 minutes

Datafeedback: –

SMJ technologies (Surface Mounted Joystick)

Change of joystick without opening the housing, easy to make a replacement service, anti twist protection
(for more information, see "Technology")

Options

LBT frequency search

When switching on or when switching the frequency, a check is made to determine whether the frequency channel used is reserved by another transmitter. If this is the case, the next frequency channel is checked until it is ensured that the transmitter can operate without faults.

LBT is short for Listen before Talk.

Machine data

Operating temperature range: -20 to +65°C

Weight: 690 g

Status indication: LEDs

Equipment safety

CE label: yes

IP-Protection Class: IP65

Power Supply

2 x AA Mignon

Battery: NiMH / 1900 mAh / 1.2 V

Battery: 1,5 V

Operating time: 40 hours

Accessories

Practical carrying system

practical carrying system with waist- and neckbelt

